



# SAFETY DATA SHEET

## 1. COMPANY AND PRODUCT INFORMATION

**Product Name:** Sundek Finish Coat

**Supplier**  
Sundeck Products USA, Inc.  
805 Ave. H Suite 508  
Arlington, Texas 76011  
**For health and safety questions:**  
Phone number (888) 390-0305  
Fax number (817) 649-7292  
E-mail: products@sundek.com

**For Chemical Emergency  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: 1-703-527-3887  
(collect calls accepted)**

## 2. HAZARDS IDENTIFICATION

GHS Pictograms:



Signal Word:

WARNING!

GHS Class:

Eye Irritant, Category 2  
Skin Irritant, Category 2

Hazard Statements:

Causes eye irritation  
Causes skin irritation

Precautionary Statements:

Wash hands thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.

Emergency Overview:

WARNING! Irritant.

Route of Exposure:

Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye:

May cause irritation.

Skin:

May cause irritation.

Inhalation:

Prolonged or excessive inhalation may cause respiratory tract irritation. Normal application procedures for this product pose no hazard as to the release of respirable titanium dioxide dust, but grinding or sanding dried films of this product may yield some respirable titanium dioxide.

Ingestion:

Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target Organs:

Eyes. Skin. Respiratory system. Digestive system.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<i>Chemical Name</i>	<i>CAS#</i>	<i>Ingredient Percent</i>	<i>EC Num.</i>
Acrylic Polymer	No Data	10 - 30 by weight	
Modified acrylic polymer(s)	No Data	1 - 5 by weight	
Talc	14807-96-6	1 - 5 by weight	
Undisclosed/Non-hazardous	No Data	1 - 5 by weight	
Water	7732-18-5	30 - 60 by weight	

### 4. FIRST-AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	First Responders should provide for their own safety prior to rendering assistance.

### 5. FIRE-FIGHTING MEASURES

Flash Point:	Not determined.
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.

Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguish Media:	Use dry chemical or foam when fighting fires involving this material. Water mist may be used to cool closed containers.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear
Unusual Fire Hazards:	Material may spatter above 100 °C/212 °F.

<b><u>NFPA Ratings:</u></b>	
NFPA Health:	1
NFPA Flammability:	1
NFPA Reactivity:	0

## 6. ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Methods for containment:	Contain spills with an inert absorbent material such as soil, sand or oil dry.
Methods for cleanup:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.

## 7. HANDLING AND STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use. Store away from direct heat or sunlight, sources of UV radiation, peroxides, or free radicals. Do not store in temperatures above 120 °F or below 48 °F. Keep away from direct sunlight.
Work Practices:	Handle in accordance with good industrial hygiene and safety practices.
Hygiene Practices:	Wash thoroughly after handling.

## 8. EXPOSURE CONTROLS, PERSONAL PROTECTION – EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer’s data for permeability data.

Hand Protection Description: Nitrile rubber or natural rubber gloves are recommended.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.



PPE Pictograms:

EXPOSURE GUIDELINES

Talc :

Guideline ACGIH: TLV-TWA: 2 mg/m3 Respirable fraction (R)
TLV-TWA: 1 mg/m3 Respirable fraction (R)

Guideline OSHA: PEL-TWA: 20 mppcf

Notes: Only established PEL and TLV values for the ingredients are listed.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical State Appearance: Liquid.
Odor: Slight
Boiling Point: Not determined.
Melting Point: 0°C (32°F)
Specific Gravity: > 1
Solubility: Miscible in water
Vapor Density: Not determined.
Vapor Pressure: Not determined.
Percent Volatile: Data not available.
Evaporation Rate: Not determined.
pH: 7.5 - 10
Flash Point: Not determined.
Auto Ignition Temperature: Not determined.

## 10. STABILITY AND REACTIVITY

Chemical Stability:	Stable under recommended handling and storage conditions.
Hazardous Polymerization:	Does not occur.
Conditions to Avoid:	Heat, flames, ignition sources and sparks. Incompatible materials. Freezing or temperatures below 32 deg. F.
Incompatible Materials:	Water reactive materials.
Special decomposition products:	Thermal decomposition can lead to release irritant fumes and toxic gases.

## 11. TOXICOLOGICAL INFORMATION

### Talc :

RTECS Number: WW2710000

Inhalation: Inhalation - Rat TCLo - Lowest published toxic concentration : 17 mg/m<sup>3</sup>/6H/26D (Intermittent) [ Lungs, Thorax, or Respiration – Other changes ]  
 Inhalation - Mouse TCLo - Lowest published toxic concentration : 20400 ug/m<sup>3</sup>/6H/26D (Intermittent) [ Lungs, Thorax, or Respiration – Other changes ] (RTECS)

## 12. ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

## 13. DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines. Triple-rinse drum prior to offering for recycle, reconditioning or disposal. Dispose of rinsate in an environmentally acceptable manner consistent with applicable waste managements.

## 14. TRANSPORT INFORMATION

DOT Shipping Name:	Non regulated.
DOT Hazard Class:	Non regulated.
IATA Shipping Name:	Non regulated.
IMDG UN Number :	Non regulated

## 15. REGULATORY INFORMATION

SARA: This product contains chemicals which are subject to the reporting requirements of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III (40CFR, Part 372).

California PROP 65: The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the State of California to cause cancer.

Canada WHMIS: Xi – Irritant

EU Class: Irritant.  
In accordance to Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures

Risk Phrases: R36/37/38 - Irritating to eyes, respiratory system and skin.

Safety Phrase: S23 - Do not breathe gas/fumes/vapour/spray.  
S37 - Wear suitable gloves.

**Talc :**

TSCA Inventory Status: Listed

Canada DSL: Listed

**16. OTHER INFORMATION**

HMIS Health Hazard: 1\*

HMIS Fire Hazard: 1

HMIS Reactivity: 0

HMIS Personal Protection: X

SDS Creation Date: October 10, 2013

SDS Revision Date: May 21, 2015

Disclaimer: The information and recommendations contained herein are, to the best of Sundeck Products knowledge and belief, accurate and reliable as of the date issued. Sundeck Products does not warrant or guarantee their accuracy or reliability, and Sundeck Products shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its particular use.