



# MATERIAL SAFETY DATA SHEET

## 1. COMPANY AND PRODUCT INFORMATION

**Product Name:** Sundek SunDye Exterior

**Supplier**  
Sundeck Products USA, Inc  
805 Ave. H Suite 508  
Arlington, Texas 76011  
For health and safety questions:  
Phone number (888) 390-0305  
Fax number (817) 649-7292  
E-mail: products@sundek.com

**For Chemical Emergency  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: 1-703-527-3887  
(collect calls accepted)**

## 2. GENERAL INFORMATION

**Product Class:** Kolor Dye

		HMIS	NFPA	NFPA RATING		
HEALTH	1	SEVERE	4	EXTREME	FIRE	2
FLAMMABILITY	2	SERIOUS	3	HIGH	REACTIVITY	0
REACTIVITY	0	MODERATE	2	MODERATE	TOXICITY	1
		SLIGHT	1	SLIGHT	SPECIAL	
		MINIMAL	0	INSIGNIFICAN		

## 3. HAZARDOUS INGREDIENTS

	<u>CAS#</u>
Light Aromatic solvent naphtha	64742-95-6
Butyl acetate	123-84-4
Threshold limit value:	150 ppm (PEL-150 ppm)

## 4. PHYSICAL DATA

<b>Boiling Point:</b>	NE	<b>Solubility in Water:</b>	Limited
<b>Vapor Pressure:</b>	NA	<b>Percent Volatile by Volume:</b>	NA
<b>Vapor Density:</b>	NA	<b>Appearance and Odor:</b>	Various colors-liquids with solvent order
<b>Specific Gravity:</b>	1.2	<b>VOC gm/L:</b>	687
<b>pH:</b>	NA		

## 5. FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** 105° F (TCC/PM)  
**Extinguishing media:** Dry chemical, water fog, CO2  
**Flammable Limits:** LEL 1.00  
UEL 7.00  
**Special Fire Fighting Procedures:** Wear full protective equipment including NIOSH approved self-contained breathing apparatus. Keep containers tightly closed and away from heat.

## 6. REACTIVITY DATA

**Stability:** Stable  
**Hazardous Polymerization:** No  
**Incompatibility:** Strong oxidizing agents

**Conditions to avoid:** High temperatures  
**Materials to avoid:** Strong oxidizing agents or bleach  
**Hazardous Decomposition:** No

### 7. HEALTH HAZARD DATA

**Primary Route of Entry:** Skin  
**Eye Contact:** Irritation, discoloration, redness.  
**Skin Contact:** Irritation and cracking of the skin may occur. Discoloration due to dyes.  
**Inhalation:** May cause dizziness and light headiness. Remove to fresh air.  
**Ingestion:** Rinse mouth with water and seek medical attention.  
**OSHA Permissible Exposure:** NA  
**ACCGIH Threshold:** NA  
**Carcinogen – NTP:** No  
**Carcinogen – IARC:** No

### 8. FIRST AID

**Eyes:** Immediately rinse with plenty of clean flowing water for at least 15 minutes, holding eyelids open to rinse completely. If irritation persists, get medical attention.  
**Skin:** Flush off with water then soap and water. Apply a good skin lotion to remove the remainder. Wash contaminated clothing before reuse.  
**Inhalation:** Move person to fresh air. Get emergency medical help immediately.  
**Ingestion:** Rinse mouth with water and get medical attention.

### 9. SPECIAL PROTECTION INFORMATION

**Ventilation:** Local exhaust is recommended  
**Eye Protection:** Safety glasses  
**Skin Protection:** Rubber or vinyl gloves  
**Other Protection:** NA

### 10. SPILL OR LEAK PROCEDURES

**Steps to be taken if material is released or spilled:** Wear protective clothing and gloves. Stop leak and contain spill. Soak up on absorbent materials and place in a sealable container.  
**Waste Disposal Method:** Dispose of in accordance with local and federal regulations.

### 11. SHIPPING DATA

**Technical Shipping Name:** Petroleum Distillates N.O.S.  
**Identification Number:** UN1268 (Exceptions – CFR49-173.150(f))  
**Freight Class:** Combustible – Not Regulated  
**Packing Group:** III

**Disclaimer:** To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.