



MATERIAL SAFETY DATA SHEET

1. COMPANY AND PRODUCT INFORMATION

Product Name: Sundek SunVap FC- Part B

Supplier
Sundeck Products USA, Inc
805 Ave. H Suite 508
Arlington, Texas 76011
For health and safety questions:
Phone number (888) 390-0305
Fax number (817) 649-7292
E-mail: products@sundek.com

**For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300
Outside USA and Canada: 1-703-527-3887
(collect calls accepted)**

2. GENERAL INFORMATION

Product Class: Aliphatic Amine Solution
HMIS Codes: H F R P
2 1 0 G

3. HAZARDOUS INGREDIENTS

	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
None			

4. PHYSICAL DATA

Boiling Point: N/A	Solubility in Water: Miscible
Vapor Pressure: N/A	Evaporation Rate: Slower Than Butyl Acetate
Vapor Density: Heavier Than Air	Appearance: Medium Viscosity Liquid
Specific Gravity: 1.03	Odor: Slight Ammonia and Solvent Odor
Percent Volatiles: 63	

5. FIRE AND EXPLOSION HAZARD DATA

Flash Point:	>200° F (SETA Flash)
Flammable Limits:	% volume in Air LEL: N/A UEL: N/A
Extinguishing media:	Water fog, "Alcohol" foam, dry chemical and CO2.
Special Fire Fighting Procedures:	Material will not burn unless preheated. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coat, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.
Fire and Explosion Hazards:	Containers exposed to intense heat from fire should be cooled with water to prevent vapor pressure build-up which could result in container rupture. Cool with large quantities of water.
Hazardous Combustion Products:	Carbon Monoxide, Aldehydes, Acids and other Organic Compounds may be formed.

6. REACTIVITY DATA

Stability:	Stable
Hazardous Polymerization:	Will not occur
Incompatibility:	Avoid heat and flames. May react vigorously with strong oxidizing agents. Epoxy resins or isocyanates. Reactions may evolve considerable heat. May react vigorously with mineral or organic acids.

7. HEALTH HAZARD DATA

Primary Route of Entry:	Dermal, Inhalation
Eye Contact:	May be severely irritating to the eyes. May cause corneal damage.
Skin Contact:	May be moderately irritating to the skin. May be toxic or harmful if absorbed thru skin. May cause skin sensitization.
Inhalation:	May cause irritation to the nose, throat and respiratory tract. May be toxic if inhaled. May cause respiratory tract sensitization.
Ingestion:	Maybe moderately toxic and may be harmful if swallowed. May produce damage to the red blood cells.

8. FIRST AID

Eyes:	Immediately flush eyes with plenty of water for at least 15 min. while holding eyelids open. Seek medical attention.
Skin:	Immediately remove contaminated clothing. Wipe excess from skin and flush with plenty of water. Use soap if available. Do not reuse clothing until thoroughly cleaned. Seek medical attention.
Ingestion:	Do not induce vomiting. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs. Seek medical attention.
Inhalation:	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Seek medical attention.

9. SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Wear NIOSH approved respirator for organic vapors to prevent overexposure.
Ventilation:	Use explosion-proof ventilation as required to control vapor concentrations.
Eye Protection:	Chemical splash goggles or other approved safety glasses.
Skin Protection:	Wear chemical resistant gloves and other clothing as required to minimize contact.

10. SPILL OR LEAK PROCEDURES**Steps to be taken if material is released or spilled:**

Large Spill:	Eliminate all ignition sources. Wear respirator and other protective clothing. Stop spill at source. Dike and contain spill. Pump or vacuum transfer spilled material to a clean recovery vessel. Soak up residue with absorbent material.
Small Spills:	Absorbent material should be used to take up the spill.
Waste Disposal Method:	Dispose of material in accordance with all federal, state and local regulations.

11. SHIPPING DATA

D.O.T. Shipping Name:	Aliphatic Amine Solution
Technical Shipping Name:	Aliphatic Amine Solution, 25%
D.O.T. Hazard Class:	Not Regulated
UN/NA Number:	N/A
Reportable Quantity:	N/A
D.O.T. Labels Required:	None
Freight Class:	55

Disclaimer:

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.