



MATERIAL SAFETY DATA SHEET

1. COMPANY AND PRODUCT INFORMATION

Product Name: Sundek SunVap Primer- Part B

Supplier
Sundeck Products USA, Inc
805 Ave. H Suite 508
Arlington, Texas 76011
For health and safety questions:
Phone number (888) 390-0305
Fax number (817) 649-7292
E-mail: products@sundek.com

**For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300
Outside USA and Canada: 1-703-527-3887
(collect calls accepted)**

2. GENERAL INFORMATION

Product Class: Modified Bisphenol F Epoxy Resin
HMIS Codes: H F R P
2 1 0 G

3. HAZARDOUS INGREDIENTS

	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Oxirane, Mono[(C12-14-alkyloxy)methyl] Dervis	68609-97-2	N/E	N/E

4. PHYSICAL DATA

Boiling Point: >300° F	Solubility in Water: Slight
Vapor Pressure: 1.3 mm Hg	Evaporation Rate: N/A
Vapor Density: Greater Than Air	Appearance: clear Light Colored Liquid
Specific Gravity: 1.15	Odor: Mild Solvent Odor
Percent Volatiles: 0	

5. FIRE AND EXPLOSION HAZARD DATA

Flash Point: >200° F (SETA Flash)

Flammable Limits: LEL: N/A
UEL: N/A

Extinguishing media: Water fog, "Alcohol" foam, dry chemical, CO2.

Special Fire Fighting Procedures: Wear full protective equipment including NIOSH approved Self-Contained breathing apparatus.

Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or moved by ventilation and ignited by an open ignition source.

Hazardous Combustion Products: Carbon Monoxide, Carbon Dioxide and Various Hydrocarbons.

6. REACTIVITY DATA

Stability:	Stable
Hazardous Polymerization:	Will not occur
Incompatibility:	Avoid contact with strong oxidizing agents. Lewis or mineral acids and strong mineral or organic bases, especially aliphatic amines. Reaction may evolve considerable heat.

7. HEALTH HAZARD DATA

Primary Route of Entry:	Dermal, Inhalation
Eye Contact:	Can cause severe irritation, redness, tearing and blurred vision.
Skin Contact:	Can cause skin irritation. May cause skin sensitization.
Inhalation:	May cause nasal and respiratory irritation. Central Nervous system effects including dizziness, weakness, nausea and headache.
Ingestion:	May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.
Chronic Overexposure:	Skin sensitization may be evidenced by rashes.

8. FIRST AID

Eyes:	Immediately flush eyes with plenty of water for at least 15 min. while holding eyelids open. Seek medical attention.
Skin:	Immediately remove contaminated clothing. Wipe excess from skin and flush with plenty of water. Use soap if available. Do not reuse clothing until thoroughly cleaned. Seek medical attention.
Ingestion:	Do not induce vomiting. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs. Seek medical attention.
Inhalation:	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Seek medical attention.

9. SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Wear NIOSH approved respirator for organic vapors to prevent overexposure.
Ventilation:	Use explosion-proof ventilations as required to control vapor concentrations.
Eye Protection:	Chemical splash goggles or other approved safety glasses.
Skin Protection:	Wear chemical resistant gloves and other clothing as required to minimize contact.

10. SPILL OR LEAK PROCEDURES**Steps to be taken if material is released or spilled:**

Large Spill:	Eliminate all ignition sources. Wear respirator and other protective clothing. Stop spill at source. Dike and contain spill. Pump or vacuum transfer spilled material to a clean recovery vessel. Soak up residue with absorbent material.
Small Spills:	Absorbent material should be used to take up the spill.
Waste Disposal Method:	Dispose of material in accordance with all federal, state and local regulations.

11. SHIPPING DATA

D.O.T. Shipping Name: Epoxy Paint
Technical Shipping Name: Epoxy Resin
D.O.T. Hazard Class: Not Regulated
UN/NA Number: N/A
Reportable Quantity: None
D.O.T. Labels Required: None
Freight Class: 55

Disclaimer:

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.