



MATERIAL SAFETY DATA SHEET

1. COMPANY AND PRODUCT INFORMATION

Product Name: Sundek Floor Wax

Supplier
Sundeck Products USA, Inc
805 Ave. H Suite 508
Arlington, Texas 76011
For health and safety questions:
Phone number (888) 390-0305
Fax number (817) 649-7292
E-mail: products@sundek.com

**For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300
Outside USA and Canada: 1-703-527-3887
(collect calls accepted)**

2. GENERAL INFORMATION

Product Class: Sundek Floor Wax

| HMIS SYMBOL | | HMIS | NFPA | NFPA RATING |
|--------------|---|----------|-----------------|--------------|
| HEALTH | 1 | SEVERE | 4 EXTREME | FIRE 0 |
| FLAMMABILITY | 0 | SERIOUS | 3 HIGH | REACTIVITY 0 |
| REACTIVITY | 0 | MODERATE | 2 MODERATE | TOXICITY 1 |
| | | SLIGHT | 1 SLIGHT | SPECIAL |
| | | MINIMAL | 0 INSIGNIFICANT | |

3. HAZARDOUS INGREDIENTS

Glycol Ethers 111-77-3 & 9111-90-0 (7% max.)
GlycolEther DPM 34590-94-8
Ammonium hydroxide 1336-21-6

Threshold Value Units:

NE
100 ppm skin
50 ppm

4. PHYSICAL DATA

| | | | |
|---------------------------|------------------|---|--------------------|
| Boiling Point: | NE | Melting Point: | N/A |
| Freezing Point: | 0 deg C/32 deg F | Solubility in Water: | Miscible |
| Physical State: | Liquid | Coefficient of Water/Oil Distribution: | N/E |
| Vapor Pressure: | NE | Evaporation Rate: | ~1 |
| Vapor Density: | >1 | Appearance: | Milky white liquid |
| Specific Gravity: | 1.03 | Odor: | Slight |
| Percent Volatiles: | ~80 | pH: | 8-9 |

5. FIRE AND EXPLOSION HAZARD DATA

Flash Point: >200°F (TCC)
Flammable Limits: Not Regulated
LEL: NE
UEL: NE

Extinguishing media: Same as suitable for the surrounding materials

Special Fire Fighting Procedures: Toxic gasses may be released during decomposition at high temperatures. Use self contained breathing apparatus.

Fire and Explosion Hazards: None known

6. REACTIVITY DATA

| | |
|--|---|
| Stability: | Stable |
| Hazardous Polymerization: | No |
| Incompatibility: | None |
| Hazardous Decomposition Products: | None known |
| Conditions to Avoid: | Temperature above 120°F (49°C) and below freezing |
| Materials to Avoid: | Strong oxidizing agents, acids, and alkali's |

7. HEALTH HAZARD DATA

| | |
|-----------------------------------|--|
| OSHA Permissible Exposure: | NE |
| Carcinogen-NTP Program: | No |
| ACFIH Threshold Limit: | NE |
| Carcinogen-IARC Program: | No |
| Primary route of entry: | Skin |
| Eye Contact: | Irritation, forms film that may stick eyelids together |
| Skin Contact: | Possible irritation |
| Inhalation: | No known effects |
| Ingestion: | Stomach upset, nausea |

8. FIRST AID

| | |
|-------------------|--|
| Eyes: | Flush thoroughly with water, lifting both eyelids. If irritation persists, seek medical attention. |
| Skin: | Wash with soap and water. Remove contaminated clothing and launder before reuse. |
| Ingestion: | Drink several glasses of water to dilute the product. Induce vomiting if directed to do so by a doctor or poison control center. Seek medical attention. |

9. SPECIAL PROTECTION INFORMATION

| | |
|-------------------------------------|--|
| Respiratory Protection: | Not required |
| Ventilation: | General mechanical |
| Eye Protection: | Recommended |
| Skin Protection: | Rubber gloves |
| Work and Hygienic Practices: | Wash hands after handling. Do not contaminate food or feedstuff. |
| Other Precautions: | Read and observe all label precautions before using. |

10. SPILL OR LEAK PROCEDURES

Steps to be taken if material is released or spilled: Small spill flush to sewer with large quantities of water. Large spills soak up on absorbent material and dispose as non-hazardous waste.

Waste Disposal Method: Observe all local and federal regulations.

Disclaimer: To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.