



MATERIAL SAFETY DATA SHEET

1. COMPANY AND PRODUCT INFORMATION

Product Name: Sundek SunClear EcoClear, Part A

Supplier
Sundeck Products USA, Inc
805 Ave. H Suite 508
Arlington, Texas 76011
For health and safety questions:
Phone number (888) 390-0305
Fax number (817) 649-7292
E-mail: products@sundek.com

**For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1 703-527-
3887 (collect calls accepted)**

2. GENERAL INFORMATION

Product Class: Polyester/Acrylic Resin Dispersion
HMIS Codes: H F R P
1 0 0 G

3. HAZARDOUS INGREDIENTS

None

4. PHYSICAL DATA

Boiling Point:	212° F	Solubility in Water:	Dispersible
Vapor Pressure:	29.33mm Hg @ 68° F	Evaporation Rate:	.38
Vapor Density:	.569	Appearance:	Light straw-colored liquid
Specific Gravity:	1.0	Odor:	Slight ammonia odor
Percent Volatiles:	75%		

5. FIRE AND EXPLOSION HAZARD DATA

Flash Point: Greater than 250° F (SETA Flash c.c.)
Flammable Limits:
LEL: 16
UEL: 25

Extinguishing media: Dry chemical, carbon dioxide, foam, water.
Hazardous Combustion Products: CO₂, CO and other aliphatic fragments.
Special Fire Fighting Procedures: Fire-fighter should wear self-contained breathing apparatus and full protective clothing. Use water spray to cool nearby containers and structures exposed to fire.

Fire and Explosion Hazards: Product will not burn but may spatter if temperature exceeds boiling points of water. Dried solids can burn giving off hazardous decomposition products. After water evaporates, remaining material will burn. Toxic gases may be generated by thermal decomposition.

6. REACTIVITY DATA

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: None known

7. HEALTH HAZARD DATA

Primary Route of Entry: Skin or eye contact, inhalation.
Eye Contact: Can cause moderate irritation.
Skin Contact: Can cause moderate irritation.
Inhalation: Can cause irritation to nasal passages; throat plus lungs.
Ingestion: Can cause gastrointestinal irritation.
Chronic Overexposure: Can cause damage to the respiratory system, lungs, eyes, skin and central nervous system.

8. FIRST AID

Eyes: Flush with clean water for at least 15 minutes.
Skin: Remove contaminated clothing. Wash affected areas with soap and water.
Ingestion: Consult physician.
Inhalation: Move to fresh air.

9. SPECIAL PROTECTION INFORMATION

Respiratory Protection: NIOSH approved organic vapor respirator should be used where ventilation is inadequate.
Ventilation: General dilution ventilation that maintains vapor levels below the appropriate exposure limit is recommended.
Eye Protection: Safety glasses or goggles are recommended.
Skin Protection: Impermeable gloves are recommended.

10. SPILL OR LEAK PROCEDURES

Steps to be taken if material is released or spilled: Cover spill with absorbent material, collect for disposal. Wash spill area with hot water.
Waste Disposal Method: Dispose of in compliance with all local, state and federal government regulations.

11. SHIPPING DATA

D.O.T. Shipping Name: Epoxy Paint
Technical Shipping Name: Polyol Solution
D.O.T. Hazard Class: Not Regulated
UN/NA Number: None
Reportable Quantity: None
D.O.T. Labels Required: None
Freight Class: 55

Disclaimer

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.