



MATERIAL SAFETY DATA SHEET

1. COMPANY AND PRODUCT INFORMATION

Product Name: Sundek SunEpoxy Crack Treatment, Part B

Supplier
Sundeck Products USA, Inc
805 Ave. H Suite 508
Arlington, Texas 76011
For health and safety questions:
Phone number (888) 390-0305
Fax number (817) 649-7292
E-mail: products@sundek.com

**For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300
Outside USA and Canada: 1-703-527-3887
(collect calls accepted)**

2. GENERAL INFORMATION

Product Class: Aliphatic Amine Adduct Solution
HMIS Codes: H F R P
3 1 0 G

3. HAZARDOUS INGREDIENTS

	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Alkyl Phenol	15520-10-2	N/E	N/E
1,5 Pentanediamine, 2-Methyl		N/E	N/E
Benzyl Alcohol	100-51-6	N/E	N/E
1,2 Diaminocyclohexane	694-83-7	N/E	N/E
Diglycidyl Ether of Bisphenol "A"	25068-38-6	N/E	N/E
Fumed Silica	112945-52-5	N/E	N/E

4. PHYSICAL DATA

Boiling Point: N/A
Vapor Pressure: 1.8 mm Hg.
Vapor Density: Greater Than Air
Specific Gravity: .99
Percent Volatiles: N/A

Solubility in Water: Moderate
Evaporation Rate: Less than Butyl Acetate
Appearance: Dark Yellow to Brown Liquid
Odor: Ammonia

5. FIRE AND EXPLOSION HAZARD DATA

Flash Point: 180° F
Flammable Limits: LEL: N/A
UEL: N/A

Extinguishing media: Water Fog, Foam, Dry Chemical or CO2.
Special Fire Fighting Procedures: Wear full protective clothing including NIOSH approved Self-Contained breathing apparatus.

Fire and Explosion Hazards: Exposure to heat will build pressure in container. Cool with water spray.
Hazardous Combustion Products: Ammonia, Oxides of Nitrogen, Toxic Fumes.

6. REACTIVITY DATA

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: Mineral acids, organic acids and strong oxidizing agents.

7. HEALTH HAZARD DATA

Primary Route of Entry:	Dermal, Inhalation, eye contact.
Eye Contact:	Exposure to liquid or vapors may cause severe eye irritation. Symptoms include tearing, redness, burning, swelling and eye damage.
Skin Contact:	May cause skin irritation. Redness, burning and skin damage.
Ingestion:	Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Inhalation:	Excessive inhalation of vapors can cause nasal and respiratory irritation, CNS effects include dizziness, weakness, nausea, headache and possible unconsciousness.
Chronic Overexposure:	May cause skin sensitization.

8. FIRST AID

Eyes:	Immediately flush eyes with copious amounts of water for 15 minutes. Seek medical attention.
Skin:	Immediately remove contaminated clothing. Wipe excess from skin. Wash with plenty of soap and water. Seek medical attention. Do not reuse clothing until thoroughly cleaned.
Ingestion:	Do not induce vomiting. Give large quantities of water. Call physician immediately.
Inhalation:	Remove victim to fresh air and provide oxygen if breathing is difficult. Seek medical attention.

Note to Physician: After ingestion, the patient may improve after the initial crisis, but perforation of gastrointestinal tract may occur 2-4 days later with severe abdominal pain, rigidity and tenderness of the abdomen and shock. Strictures of the esophagus may occur.

9. SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Use appropriate NIOSH approved respirator for organic vapor to prevent overexposure.
Ventilation:	Provide sufficient ventilation to maintain exposure below level of overexposure.
Eye Protection:	Chemical goggles and full face shield.
Skin Protection:	Wear chemical resistant gloves and other clothing as required to prevent any contact with the skin.

10. SPILL OR LEAK PROCEDURES

Steps to be taken if material is released or spilled:

Ventilate spill area. Cover with inert, absorbent material and remove to disposal container. Observe all federal, state and local regulations. Do not flush to surface water or sanitary sewer.

Waste Disposal Method: Dispose of waste in accordance to federal, state and local regulations.

11. SHIPPING DATA

D.O.T. Shipping Name:	Amines, Liquid Corrosive N.O.S.
Technical Shipping Name:	Aliphatic Amine
D.O.T. Hazard Class:	8 Corrosive Liquid
UN/NA Number:	UN2735
Reportable Quantity:	N/A
D.O.T. Labels Required:	Corrosive
Shipping Class:	55
Packing Group:	III

Disclaimer:

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.