



SAFETY DATA SHEET

1. COMPANY AND PRODUCT INFORMATION

Product Name: Sundek SunSeal A18

Supplier
Sundeck Products USA, Inc.
805 Ave. H Suite 508
Arlington, Texas 76011
For health and safety questions:
Phone number (888) 390-0305
Fax number (817) 649-7292
E-mail: products@sundek.com

**For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300
Outside USA and Canada: 1-703-527-3887
(collect calls accepted)**

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 5
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 2
Flammable liquids Category 2, Hazardous to the Aquatic Environment - Long Term (Chronic) Hazard Category 2	

Label elements

Emergency Overview

Danger!

Hazard statements

Highly flammable
Suspected of Causing Cancer
Toxic to Aquatic Life with Long Lasting Effects
Causes Serious Eye Irritation
May Cause Respiratory Irritation
May Cause Drowsiness or Dizziness
May be Harmful if Swallowed
May be Harmful if Swallowed and Enters Airways
Causes Skin Irritation



Appearance Transparent Liquid

Physical state liquid

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ ventilating / lighting/ .? / equipment
 Use only non-sparking tools
 Take action to prevent static discharges
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Use only outdoors or in a well-ventilated area
 Avoid release to the environment
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
 If skin irritation occurs: Get medical advice or attention.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
 IF SWALLOWED: Immediately call a POISON CONTROL CENTER/doctor
 Do NOT induce vomiting.
 Take off contaminated clothing and wash before reuse
 In case of fire use, "alcohol resistant" foam, dry chemical, halon or carbon dioxide to extinguish.
 Collect spillage

Precautionary Statements - Storage

Store in well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
Xylene	1330-20-7	30 - 60	*
Acetone	67-64-1	15 - 40	*
Poly (methyl methacrylate/n-Butyl methacrylate/Methacrylic acid)	28262-63-7	10 - 30	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Description of first aid measures**General advice**

Move out of the dangerous area. Consult a physician. Provide this Safety Data Sheet to the doctor in attendance.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.

Ingestion IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Symptoms Eye, Skin, and Respiratory Irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically. For additional information, see Safety Data Sheet.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry Chemical, Alcohol Resistant Foam, Halon or Carbon Dioxide.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

In a fire or if heated a pressure increase may occur and the container may burst.

Hazardous combustion products Carbon dioxide (CO₂). Carbon monoxide.

Explosion data

Sensitivity to Mechanical Impact Not available.

Sensitivity to Static Discharge May be ignited by friction, heat, sparks or flames.

Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not allow product to enter any drains or waterways.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike to collect large liquid spills.

Methods for cleaning up Use a non-combustible material like vermiculite or sand to soak up the product and place into a container for later disposal. Use clean non-sparking tools to collect absorbed material. Dispose according to local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take measures to prevent the buildup of electrostatic charge. Use non-sparking tools. Wash hands and skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Incompatible materials Keep away from strong oxidizing agents, strong alkalis, and strong acids.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION – EXPOSURE GUIDELINES**Control parameters**

Exposure Guidelines Poly (methyl methacrylate/n-Butyl methacrylate/Methacrylic acid) - CAS# 28262-63-7: None Established. Acetone - CAS# 67-64-1: UK. EH40 WEL TWA 500 ppm 8 hours, STEL 1500 ppm 15 minutes. Xylene, Mixed Isomers, CAS# 1330-20-7, TWA 100 ppm ACGIH 8 hrs., STEL 150 ppm ACGIH 15 min., PEL 100ppm OSHA 8 hrs.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³

Appropriate engineering controls

Engineering Controls General/Local Ventilation Recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear chemical resistant gloves at minimum. Wash skin immediately upon contact. Wash hands at mealtime and end of shift.

Respiratory protection Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before and after breaks and at the end of the work day.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	liquid	Odor	Solvent
Appearance	Transparent Liquid	Odor threshold	No data available
Color	Transparent Liquid - May have slight color due to performance additives.		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not Relevant	
Melting point / freezing point	Not Available	

Boiling point / boiling range	149 °C	
Flash point	-18.9 °C (< -2 °F)	CC (closed cup)
Evaporation rate	Not Available	
Flammability (solid, gas)	Not Relevant	
Flammability Limit in Air		
Upper flammability limit:	7.0%	
Lower flammability limit:	1.0%	
Vapor pressure	Not Available	
Vapor density	Not Available	
Relative density	.86 @ 70 Degrees F	
Water solubility	Insoluble in water	
Solubility in other solvents	Not Available	
Partition coefficient	Not Available	
Autoignition temperature	Not Available	
Decomposition temperature	Not Available	
Kinematic viscosity	Not Available	
Dynamic viscosity	Not Available	
Explosive properties	Not Available	
Oxidizing properties	Not Available	

Other Information

Softening point	Not Relevant
Molecular weight	Not Available
VOC Content (%)	< 700 g/L
Density	Not Available
Bulk density	Not Available

10. STABILITY AND REACTIVITY

Reactivity

Not Available

Chemical stability

Stable.

Possibility of Hazardous Reactions

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Keep away from strong oxidizing agents, strong alkalis, and strong acids.

Hazardous Decomposition Products

Hazardous decomposition products formed under fire conditions, carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	Direct contact and vapor inhalation.
Eye contact	Direct contact.
Skin contact	Direct contact.
Ingestion	Direct contact.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 4300 mg/kg (Rat)	-	= 47635 mg/L (Rat) 4 h
Acetone 67-64-1	-	-	= 50100 mg/m ³ (Rat) 8 h

Information on toxicological effects

Symptoms May cause drowsiness or dizziness if inhaled. May cause respiratory irritation. Causes serious eye irritation. Causes skin irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes severe burns. Irritating to skin.
Serious eye damage/eye irritation Irritating to eyes. Risk of serious damage to eyes.
Irritation Irritating to eyes, respiratory system and skin.
Sensitization No data available.
Germ cell mutagenicity No data available.
Carcinogenicity Naphtha (petroleum), heavy aromatic (CAS#64742-94-5) Contains an ingredient, Cumene which is classified by IARC as "possibly carcinogenic to humans" (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-

Reproductive toxicity Not Available.
STOT - single exposure Not Available.
STOT - repeated exposure Not Available.
Aspiration hazard Not Available.

Numerical measures of toxicity - Product Information**12. ECOLOGICAL INFORMATION**

Material is expected to be harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Xylene 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Acetone 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No data available.

Bioaccumulation

No data available.

Chemical Name	Partition coefficient
Xylene 1330-20-7	2.77 - 3.15
Acetone 67-64-1	-0.24

Other adverse effects

No data available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Under RCRA 40 CFR 261 this material is a hazardous waste. Dispose of in accordance with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for information on waste disposal in your area. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of in accordance with federal, state and local regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Acetone 67-64-1	-	Included in waste stream: F039	-	U002

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Acetone 67-64-1	Ignitable

14. TRANSPORT INFORMATION

DOT
Marine pollutant UN1263, PAINT RELATED MATERIAL, 3, II
Material is expected to be harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

IATA UN1263, PAINT RELATED MATERIAL, 3, II

IMDG UN1263, PAINT RELATED MATERIAL, 3, II

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains chemicals known to the state of California to cause birth defects or other reproductive harm

U.S. State Right-to-Know Regulations

U.S. EPA Label Information

16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection X

Issue Date 12-May-2015
Revision Date 27-May-2015
Revision Note
 No data available

Disclaimer: The information and recommendations contained herein are, to the best of Sundeck Products knowledge and belief, accurate and reliable as of the date issued. Sundeck Products does not warrant or guarantee their accuracy or reliability, and Sundeck Products shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its particular use.