



# MATERIAL SAFETY DATA SHEET

## 1. COMPANY AND PRODUCT INFORMATION

**Product Name:** Sundek SunStain SunH<sub>2</sub>O P

**Supplier**  
Sundeck Products USA, Inc  
805 Ave. H Suite 508  
Arlington, Texas 76011  
For health and safety questions:  
Phone number (888) 390-0305  
Fax number (817) 649-7292  
E-mail: products@sundek.com

**For Chemical Emergency  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: 1-703-527-3887  
(collect calls accepted)**

## 2. GENERAL INFORMATION

**Product Class:** Acrylic Latex  
**HMIS Codes:** H F R P  
1 0 0 B

## 3. HAZARDOUS INGREDIENTS

|                           | <u>CAS#</u> | <u>OSHA PEL</u> | <u>ACGIH TLV</u> |
|---------------------------|-------------|-----------------|------------------|
| Talc                      | 14807-96-6  | N/E             | N/E              |
| Ethylene Glycol           | 107-21-1    | N/E             | N/E              |
| Ethoxylated Dodecylphenol | 9014-92-0   | N/E             | N/E              |
| Carbon Black              | 1333-86-4   | N/E             | N/E              |
| Diethylene Glycol         | 111-46-6    | N/E             | N/E              |

## 4. PHYSICAL DATA

|                           |                      |                             |                     |
|---------------------------|----------------------|-----------------------------|---------------------|
| <b>Boiling Point:</b>     | Same as Water        | <b>Solubility in Water:</b> | Dilutable           |
| <b>Vapor Pressure:</b>    | Same as Water        | <b>Evaporation Rate:</b>    | < 1 (Butyl Acetate) |
| <b>Vapor Density:</b>     | < 1 Lighter than air | <b>Appearance:</b>          | White milky fluid   |
| <b>Specific Gravity:</b>  | 1.02                 | <b>Odor:</b>                | Very Mild           |
| <b>Percent Volatiles:</b> | 73%                  |                             |                     |

## 5. FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** None Determined (Aqueous System)  
**Flammable Limits:** LEL: N/A  
UEL: N/A

**Extinguishing media:** Non-Flammable.

**Special Fire Fighting Procedures:** Breathing apparatus when fighting fires in enclosed area.

**Fire and Explosion Hazards:** Product will not burn but may spatter if temperature exceeds the boiling point of water. Dried solids can burn releasing oxides of carbon.

**Hazardous Combustion Products:** Possible oxides of carbon if dried solids are burned..

## 6. REACTIVITY DATA

**Stability:** Highly Stable  
**Hazardous Polymerization:** Will not occur  
**Incompatibility:** No known "conditions or materials to avoid".

**7. HEALTH HAZARD DATA**

|                                |   |
|--------------------------------|---|
| <b>Primary Route of Entry:</b> | Skin or eye contact, inhalation.  |
| <b>Eye Contact:</b>            | Direct contact may cause eye irritation.  |
| <b>Skin Contact:</b>           | Prolonged contact may cause transient reddening of the skin.  |
| <b>Ingestion:</b>              | No evidence of adverse effects.   |
| <b>Inhalation:</b>             | Trace components vapors may be irritating to eyes, mucous membrane, respiratory tract and produce headache or nausea. |
| <b>Chronic Overexposure:</b>   | None  |

**8. FIRST AID**

|                    |   |
|--------------------|---|
| <b>Eyes:</b>       | Flush eyes with water until water is no longer cloudy.                              |
| <b>Skin:</b>       | Wash skin with soap and water. If clothes are soaked, remove and wash before reuse. |
| <b>Ingestion:</b>  | No harmful effects expected.  |
| <b>Inhalation:</b> | No emergency care anticipated.  |

**Note to Physician:** There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition.

**9. SPECIAL PROTECTION INFORMATION**

|                                |  |
|--------------------------------|--|
| <b>Respiratory Protection:</b> | None should be required. Use NIOSA approved respirator in poorly ventilated areas. |
| <b>Ventilation:</b>            | General mechanical room ventilation is adequate.                                   |
| <b>Eye Protection:</b>         | Use safety glasses.  |
| <b>Skin Protection:</b>        | Gloves impervious to soap and water.   |

**10. SPILL OR LEAK PROCEDURES****Steps to be taken if material is released or spilled:**

Restrict area to only those personnel needed. Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by state, federal and local regulations.

**Waste Disposal Method:** Incinerate or bury in suitable landfill.

**11. SHIPPING DATA**

|                                 |                        |
|---------------------------------|------------------------|
| <b>D.O.T. Shipping Name:</b>    | Paint Related Material |
| <b>Technical Shipping Name:</b> | Acrylic Latex          |
| <b>D.O.T. Hazard Class:</b>     | Not Regulated          |
| <b>UN/NA Number:</b>            | N/A                    |
| <b>Reportable Quantity:</b>     | None                   |
| <b>D.O.T. Labels Required:</b>  | None                   |
| <b>Freight Class:</b>           | 55                     |

**Disclaimer:**

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.