



MATERIAL SAFETY DATA SHEET

1. COMPANY AND PRODUCT INFORMATION

Product Name: Sundek SunStain SunH₂O P

Supplier
Sundeck Products USA, Inc
805 Ave. H Suite 508
Arlington, Texas 76011
For health and safety questions:
Phone number (888) 390-0305
Fax number (817) 649-7292
E-mail: products@sundek.com

**For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300
Outside USA and Canada: 1-703-527-3887
(collect calls accepted)**

2. GENERAL INFORMATION

Product Class: Acrylic Latex
HMIS Codes: H F R P
1 0 0 B

3. HAZARDOUS INGREDIENTS

	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Talc	14807-96-6	N/E	N/E
Ethylene Glycol	107-21-1	N/E	N/E
Ethoxylated Dodecylphenol	9014-92-0	N/E	N/E
Carbon Black	1333-86-4	N/E	N/E
Diethylene Glycol	111-46-6	N/E	N/E

4. PHYSICAL DATA

Boiling Point:	Same as Water	Solubility in Water:	Dilutable
Vapor Pressure:	Same as Water	Evaporation Rate:	< 1 (Butyl Acetate)
Vapor Density:	< 1 Lighter than air	Appearance:	White milky fluid
Specific Gravity:	1.02	Odor:	Very Mild
Percent Volatiles:	73%		

5. FIRE AND EXPLOSION HAZARD DATA

Flash Point: None Determined (Aqueous System)
Flammable Limits: LEL: N/A
UEL: N/A

Extinguishing media: Non-Flammable.

Special Fire Fighting Procedures: Breathing apparatus when fighting fires in enclosed area.

Fire and Explosion Hazards: Product will not burn but may spatter if temperature exceeds the boiling point of water. Dried solids can burn releasing oxides of carbon.

Hazardous Combustion Products: Possible oxides of carbon if dried solids are burned..

6. REACTIVITY DATA

Stability: Highly Stable
Hazardous Polymerization: Will not occur
Incompatibility: No known "conditions or materials to avoid".

7. HEALTH HAZARD DATA

Primary Route of Entry:	Skin or eye contact, inhalation.
Eye Contact:	Direct contact may cause eye irritation.
Skin Contact:	Prolonged contact may cause transient reddening of the skin.
Ingestion:	No evidence of adverse effects.
Inhalation:	Trace components vapors may be irritating to eyes, mucous membrane, respiratory tract and produce headache or nausea.
Chronic Overexposure:	None

8. FIRST AID

Eyes:	Flush eyes with water until water is no longer cloudy.
Skin:	Wash skin with soap and water. If clothes are soaked, remove and wash before reuse.
Ingestion:	No harmful effects expected.
Inhalation:	No emergency care anticipated.

Note to Physician: There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition.

9. SPECIAL PROTECTION INFORMATION

Respiratory Protection:	None should be required. Use NIOSA approved respirator in poorly ventilated areas.
Ventilation:	General mechanical room ventilation is adequate.
Eye Protection:	Use safety glasses.
Skin Protection:	Gloves impervious to soap and water.

10. SPILL OR LEAK PROCEDURES

Steps to be taken if material is released or spilled:

Restrict area to only those personnel needed. Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by state, federal and local regulations.

Waste Disposal Method: Incinerate or bury in suitable landfill.

11. SHIPPING DATA

D.O.T. Shipping Name:	Paint Related Material
Technical Shipping Name:	Acrylic Latex
D.O.T. Hazard Class:	Not Regulated
UN/NA Number:	N/A
Reportable Quantity:	None
D.O.T. Labels Required:	None
Freight Class:	55

Disclaimer:

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.