



# MATERIAL SAFETY DATA SHEET

## 1. COMPANY AND PRODUCT INFORMATION

**Product Name:** Sundek SunVap Joint Filler- Part B

**Supplier**  
Sundeck Products USA, Inc  
805 Ave. H Suite 508  
Arlington, Texas 76011  
For health and safety questions:  
Phone number (888) 390-0305  
Fax number (817) 649-7292  
E-mail: products@sundek.com

**For Chemical Emergency  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night**

**Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: 1-703-527-3887  
(collect calls accepted)**

## 2. GENERAL INFORMATION

**Product Class:** Amine Blend  
**HMIS Codes:** H F R P  
3 1 0 G

## 3. HAZARDOUS INGREDIENTS

	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Ethylene Diamine	107-15-3	N/E	N/E
1,3 Cyclohexanedimrthamine	2579-20-6	N/E	N/E
Tris -2,4,6- (Dimethyaminomethyl) Phenol	90-72-2	N/E	N/E
Benzyl Alcohol	100-51-6	N/E	N/E
Diglycidyl Ether of Bisphenol A	25068-38-6	N/E	N/E

## 4. PHYSICAL DATA

**Boiling Point:** N/A  
**Vapor Pressure:** N/A  
**Vapor Density:** Heavier Than Air  
**Specific Gravity:** 1.01  
**Percent Volatiles:** N/A

**Solubility in Water:** Moderate  
**Evaporation Rate:** N/A  
**Appearance:** Yellow to Brown Liquid  
**Odor:** Ammonia

## 5. FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** >180° F  
**Flammable Limits:**  
**LEL:** N/A  
**UEL:** N/A

**Extinguishing media:** Water fog, "Alcohol" foam, dry chemical, CO2.  
**Special Fire Fighting Procedures:** Wear full protective equipment including NIOSH approved Self-Contained breathing apparatus.

**Fire and Explosion Hazards:** Exposure to heat will build pressure in container. Cool with water spray.  
**Hazardous Combustion Products:** Ammonia, Oxides of Nitrogen, Toxic Fumes.

**6. REACTIVITY DATA**

<b>Stability:</b>	Stable
<b>Hazardous Polymerization:</b>	Will not occur
<b>Incompatibility:</b>	Mineral acids, organic acids and strong oxidizing agents.

**7. HEALTH HAZARD DATA**

<b>Primary Route of Entry:</b>	Dermal, Inhalation, eye contact.
<b>Eye Contact:</b>	Exposure to liquid or vapors may cause severe eye irritation. Symptoms include tearing, redness, burning, swelling and eye damage.
<b>Skin Contact:</b>	May cause skin irritation. Redness, burning and skin damage.
<b>Inhalation:</b>	Excessive inhalation of vapors can cause nasal and respiratory irritation, CNS effects include dizziness, weakness, nausea, headache and possible unconsciousness.
<b>Ingestion:</b>	May cause gastrointestinal irritation including nausea, vomiting and diarrhea.
<b>Chronic Overexposure:</b>	May cause skin sensitization.

**8. FIRST AID**

<b>Eyes:</b>	Immediately flush eyes with plenty of water for at least 15 min. while holding eyelids open. Seek medical attention.
<b>Skin:</b>	Immediately remove contaminated clothing. Wipe excess from skin and flush with plenty of water. Use soap if available. Do not reuse clothing until thoroughly cleaned. Seek medical attention.
<b>Ingestion:</b>	Do not induce vomiting. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs. Seek medical attention.
<b>Inhalation:</b>	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Seek medical attention.

Note to Physician: After ingestion, the patient may improve after the initial crisis, but perforation of gastrointestinal tract may occur 2-4 days later with severe abdominal pain, rigidity and tenderness of the abdomen and shock. Strictures of the esophagus may occur

**9. SPECIAL PROTECTION INFORMATION**

<b>Respiratory Protection:</b>	Wear NIOSH approved respirator for organic vapors to prevent overexposure.
<b>Ventilation:</b>	Provide sufficient ventilation to maintain exposure below level of overexposure.
<b>Eye Protection:</b>	Chemical splash goggles or other approved safety glasses.
<b>Skin Protection:</b>	Wear chemical resistant gloves and other clothing as required to minimize contact.

**10. SPILL OR LEAK PROCEDURES****Steps to be taken if material is released or spilled:**

<b>Large Spill:</b>	Eliminate all ignition sources. Wear respirator and other protective clothing. Stop spill at source. Dike and contain spill. Pump or vacuum transfer spilled material to a clean recovery vessel. Soak up residue with absorbent material.
<b>Small Spills:</b>	Absorbent material should be used to take up the spill.
<b>Waste Disposal Method:</b>	Dispose of material in accordance with all federal, state and local regulations. Do not contaminate any lakes, streams, pond or underground water supply.

**11. SHIPPING DATA**

**D.O.T. Shipping Name:** Amines, Liquid Corrosive N.O.S.  
**Technical Shipping Name:** Aliphatic Amine  
**D.O.T. Hazard Class:** 8 Corrosive Liquid  
**UN/NA Number:** UN2735  
**Reportable Quantity:** N/A  
**D.O.T. Labels Required:** Corrosive  
**Freight Class:** 55  
**Packing Group:** III

**Disclaimer:**

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.